

## Minifile Openlight suspension

code MO040.840/01



### PRODUCT DESCRIPTION

Lamp with direct and diffused light from indoor suspension made of extruded aluminum 6060; complete with led; color rendering index CRI >90. Professional LED modules assembled and wired on extruded aluminum heatsink equipped with harmonic steel springs for installation in the profile Tools free, wiring through 5 cables with quick-release terminal blocks; protocol On/Off. Lamp with color finish white; white opal polycarbonate screen. Degree of protection IP40.

### PRODUCT SPECS

|                              |                       |
|------------------------------|-----------------------|
| Installation method          | Suspension            |
| Light source                 | LED                   |
| Absorbed power               | 12,8 W                |
| Color temperature            | 4000K                 |
| Color rendering index CRI    | >90                   |
| Finishing                    | White                 |
| Luminous flux of the product | 1236 lm               |
| Luminous efficiency          | 97 lm/W               |
| MacAdam color tolerance      | 3                     |
| Life time estimate           | 50000h Ta 25° L80 B10 |
| Protocol                     | On/Off                |
| Energy efficiency class      | E                     |
| Dimension                    | L580 mm               |
| IP Grade                     | IP40                  |
| Power supply                 | 220-240V 50-60Hz      |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

