



Minifile Openlight suspension

code MO041.840/01



PRODUCT DESCRIPTION

Lamp with direct and diffused light from indoor suspension made of extruded aluminum 6060; complete with led; color rendering index CRI >90. Professional LED modules assembled and wired on extruded aluminum heatsink equipped with harmonic steel springs for installation in the profile Tools free, wiring through 5 cables with quick-release terminal blocks; protocol On/Off. Lamp with color finish white; white opal polycarbonate screen. Degree of protection IP40.

PRODUCT SPECS

Installation method	Suspension
Light source	LED
Absorbed power	19,2 W
Color temperature	4000K
Color rendering index CRI	>90
Finishing	White
Luminous flux of the product	1854 lm
Luminous efficiency	97 lm/W
MacAdam color tolerance	3
Life time estimate	50000h Ta 25° L80B10
Protocol	On/Off
Energy efficiency class	E
Dimension	L860 mm
IP Grade	IP40
Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.

Page 1 / 1