



## Minifile Openlight suspension

code MO043.830D/01



### PRODUCT DESCRIPTION

Lamp with direct and diffused light from indoor suspension made of extruded aluminum 6060; complete with led; color rendering index CRI >90. Professional LED modules assembled and wired on extruded aluminum heatsink equipped with harmonic steel springs for installation in the profile Tools free, wiring through 5 cables with quick-release terminal blocks; protocol Dimmable Dali. Lamp with color finish white; white opal polycarbonate screen. Degree of protection IP40.

### PRODUCT SPECS

|                              |                      |
|------------------------------|----------------------|
| Installation method          | Suspension           |
| Light source                 | LED                  |
| Absorbed power               | 32 W                 |
| Color temperature            | 3000K                |
| Color rendering index CRI    | >90                  |
| Finishing                    | White                |
| Luminous flux of the product | 3000 lm              |
| Luminous efficiency          | 94 lm/W              |
| MacAdam color tolerance      | 3                    |
| Life time estimate           | 50000h Ta 25° L80B10 |
| Protocol                     | Dimmable Dali        |
| Energy efficiency class      | E                    |
| Dimension                    | L1420 mm             |
| IP Grade                     | IP40                 |
| Power supply                 | 220-240V 50-60Hz     |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

