

Microfile Trimless Recessed

code MF051.827/01



















PRODUCT DESCRIPTION


Direct light recessed flush mounted made of extruded aluminum 6060, square section measuring 19,8x19,5 mm; complete with led; CRI color rendering index >90. Professional led modules 19.8 W assembled and wired; protocol vedi alimentatore. Epoxy powder coated, white color finish; complete with polycarbonate [diffusore] with diffusing film. Degree of protection IP40.

PRODUCT SPECS

Installation method	Trimless recessed
Light source	Linea Led
Absorbed power	19,8 W
Color temperature	2700K
Color rendering index CRI	>90
Finishing	White
Luminous flux of the product	1004 lm
Luminous efficiency	51 lm/W
Protocol	On/Off
Energy efficiency class	D
Weight	0.35 Kg
Dimension	L925 mm
Hole size	25xL+2 mm
IP Grade	IP40
Protection Class	Class III appliance
Product Spec	Walk-over
Power supply/Transformer	Not included
Protocol	See power supply



19,5



WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

