

# **Mini Sight Minimal 2M**

code MS60.9TWS/01



350


















# PRODUCT DESCRIPTION

Square recessed fixture without frame, 2 lamps. Adjustable pull-out optic

#### **PRODUCT SPECS**

Installation method	Trimless recessed
Light source	LED
Absorbed power	2x12 W / 2x18 W
Color temperature	Tunable White
Color rendering index CRI	>90
Optic	Spot 15°
Finishing	White
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	1.05 Kg
Dimension	L193xW96xH135 Ø55 mm
IP Grade	IP20
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply



## **WEB PAGE**







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

### **MANDATORY ACCESSORIES**


## Box mini sight 2M

#### code MSC12

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit the article MINI INCAS  $2\mathsf{M}$ 



## Accessori Wallbox Frame for Mini sight 2M



#### code MSC22

inspectaBle Frame to Be Fixed and plastered in 15mm height plasterBoard False ceilings



