

# **Mini Sight Minimal 4M**

code MS80.935W/01



350



















## **PRODUCT DESCRIPTION**

Square recessed fixture without frame, 4 lamps. Adjustable pull-out optic

## **PRODUCT SPECS**

Installation method	Trimless recessed
Light source	LED
Absorbed power	4x12 W / 4x18 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Wide 46°
Finishing	White
Luminous flux of the product	5156 lm / 6413 lm
Luminous efficiency	107 lm/W / 89 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	1.85 Kg
Dimension	L193xW193xH135 Ø55 mm
Hole size	vedi accessori mm
Hole size IP Grade	IP20
. 1010 0.20	
IP Grade	IP20
IP Grade Protection Class	IP20 Class III appliance





#### **WEB PAGE**








Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

## **MANDATORY ACCESSORIES**

# Accessori Wallbox Frame for Mini sight 4M


## code MSC24



inspectaBle Frame to Be Fixed and plastered in 15mm height plasterBoard False ceilings

# **Technical Sheet**

## Box mini sight 4M



#### code MSC14

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit the article MINI INCAS 4M



