




Sight Minimal 3M

code LT4309M.940F/01



PRODUCT DESCRIPTION

Recessed downlight for wall and ceiling installation, IP20/IP23, adjustable, for accent lighting. Available in version with frame or trimless. Body optical group and frame in painted or chromed metal. Optical group adjustable 355° vertically and +/- 40° horizontally. Remote power-supply available as an accessory. Multi-lamp models set up for separate switching. It can also be completed with painted metal box for ceiling and hanging installation. It can also be installed in concrete or brick walls through specific galvanized steel wall-box, available as an accessory.

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	3x17 W / 3x24,3 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 24°
Finishing	White
Luminous flux of the product	5796 lm / 8224 lm
Luminous efficiency	114 lm/W / 113 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 ta 25°C
Protocol	On/Off
Energy efficiency class	D / E
Dimension	L460xW159xH177 mm
IP Grade	IP20
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply

WEB PAGE



ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Accessori Wallbox Frame Incas 3AM



code TEIN03M

Inspectable frame to be fit plaster in plasterboard 15mm thick for the article INCAS 3M, INCAS 3AM.
For plasterboard 13 mm tick it is necessary thicken.

Technical Sheet

