


Incas Led Minimal 2

code IN02M.940W/01



PRODUCT DESCRIPTION

Family of adjustable recessed downlight, with COB LED source, with or without frame. Square or rectangular painted steel structure with one or more light sources. Cardanic optical assembly with $\pm 25^\circ$ orientation on the two horizontal axes. The frameless version necessarily requires a subframe for installation on 13mm plasterboard false ceilings. Equipped with high-performance LEDs, with CRI > 90, high-performance passive heatsink in black anodized extruded aluminum and 99.99% pure aluminum metallized reflector. To be associated with remote stabilized current drivers. IP20.

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	2x17 W / 2x24,3 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Wide 38°
Finishing	White
Luminous flux of the product	4064 lm / 5711 lm
Luminous efficiency	120 lm/W / 118 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 ta 25°C
Protocol	On/Off
Energy efficiency class	D / E
Dimension	L159xW308xH140 mm
Hole size	vedi accessori mm
IP Grade	IP20
Protection Class	Class III appliance
Product Spec	Adjustable
Power supply/Transformer	Not included
Protocol	See power supply

WEB PAGE




ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Accessori Wallbox Frame Incas 2AM



code TEIN02M

Inspectable frame to be fit plaster in plasterboard 15mm thick for the article INCAS 12M, INCAS 2AM.
For plasterboard 13 mm tick it is necessary thicken.

Technical Sheet

