



Iride Base 114L

code IR06.927WD/01



















PRODUCT DESCRIPTION

Wall/ceiling projector with fixed projection, complete with LED 26 W beam 36°, color rendering index CRI >90. Lamp with color finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

Light source LED Absorbed power 26 W Color temperature 2700K Color rendering index CRI >90 Optic Wide 36° Finishing White Luminous flux of the product 2008 lm Luminous efficiency 77 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Protocol Dimmable Dali
Color temperature 2700K Color rendering index CRI >90 Optic Wide 36° Finishing White Luminous flux of the product 2008 Im Luminous efficiency 77 Im/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Color rendering index CRI >90 Optic Wide 36° Finishing White Luminous flux of the product 2008 lm Luminous efficiency 77 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Optic Wide 36° Finishing White Luminous flux of the product 2008 lm Luminous efficiency 77 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Finishing White Luminous flux of the product 2008 lm Luminous efficiency 77 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Luminous flux of the product 2008 lm Luminous efficiency 77 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Luminous efficiency 77 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Life time estimate 3SDCM 50000h L90 B10 Ta 25°C
Life time estimate Ta 25°C
Protocol Dimmable Dali
Energy efficiency class E
Dimension Ø114 mm
IP Grade IP20
Product Spec Adjustable
Power supply 220-240V 50-60Hz

WEB PAGE



ASSEMBLY

