



Iride Base 86L

code IR04.927F/01



















PRODUCT DESCRIPTION

Wall/ceiling projector with fixed projection, complete with LED 18 W beam 24°, color rendering index CRI >90. Lamp with color finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 ?. on the vertical axis and 90 ?. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

PRODUCT SPECS

Light source Absorbed power Color temperature Color rendering index CRI Optic Finishing Luminous flux of the product Luminous efficiency MacAdam color telegrapes LED 18 W Frook Flood 24° Flood 24°	Installation method	Wall surface mounted, Ceiling surface mounted
Color temperature 2700K Color rendering index CRI >90 Optic Flood 24° Finishing White Luminous flux of the product 1832 Im Luminous efficiency 102 Im/W	Light source	LED
Color rendering index CRI >90 Optic Flood 24° Finishing White Luminous flux of the product 1832 Im Luminous efficiency 102 Im/W	Absorbed power	18 W
Optic Flood 24° Finishing White Luminous flux of the product 1832 Im Luminous efficiency 102 Im/W	Color temperature	2700K
Finishing White Luminous flux of the product 1832 Im Luminous efficiency 102 Im/W	Color rendering index CRI	>90
Luminous flux of the product 1832 lm Luminous efficiency 102 lm/W	Optic	Flood 24°
Luminous efficiency 102 lm/W	Finishing	White
,	Luminous flux of the product	1832 lm
MacAdam color tolorance 3	Luminous efficiency	102 lm/W
iviacAdam color tolerance 3	MacAdam color tolerance	3
Life time estimate 50000h Ta 25° L80B10	Life time estimate	50000h Ta 25° L80B10
Protocol On/Off	Protocol	On/Off
Energy efficiency class D	Energy efficiency class	D
Dimension Ø86 mm	Dimension	Ø86 mm
IP Grade IP20	IP Grade	IP20
Product Spec Adjustable	Product Spec	Adjustable
Power supply 220-240V 50-60Hz	Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY

