

## Iride Track 114L

code IR17.935FD/01




### PRODUCT DESCRIPTION

Projector for track System indoor tilting/ adjustable complete with led 34 W, beam 24°, color rendering index CRI>90. Color finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 °. on the vertical axis and 90 °. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

### PRODUCT SPECS

|                              |                                 |
|------------------------------|---------------------------------|
| Installation method          | Track                           |
| Light source                 | LED                             |
| Absorbed power               | 34 W                            |
| Color temperature            | 3500K                           |
| Color rendering index CRI    | >90                             |
| Optic                        | Flood 24°                       |
| Finishing                    | White                           |
| Luminous flux of the product | 2942 lm                         |
| Luminous efficiency          | 87 lm/W                         |
| MacAdam color tolerance      | 3                               |
| Life time estimate           | 3SDCM 50000h L90 B10<br>Ta 25°C |
| Protocol                     | Dimmable Dali                   |
| Energy efficiency class      | D                               |
| Dimension                    | Ø114 mm                         |
| Product Spec                 | Adjustable                      |
| Power supply                 | 220-240V 50-60Hz                |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS

