

## Iride Outdoor 114L

code IR06IP.940S/01



### PRODUCT DESCRIPTION

Outdoor ceiling/wall projector complete with led 26 W, beam 18°, colour rendering index CRI>90. Colour finish white. Body lamp and optical group made of die-cast aluminum powder-coated, aluminum joint, rotation of the optical group of 355 °. on the vertical axis and 90 °. on the horizontal axis. Snooter in lamp finish or finishing choice. High performance lens. Possibility of insertion of Honey Comb filter.

### PRODUCT SPECS

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| Installation method          | Wall surface mounted,<br>Ceiling surface mounted |
| Light source                 | LED                                              |
| Absorbed power               | 26 W                                             |
| Color temperature            | 4000K                                            |
| Color rendering index CRI    | >90                                              |
| Optic                        | Spot 18°                                         |
| Finishing                    | White                                            |
| Luminous flux of the product | 2333 lm                                          |
| Luminous efficiency          | 90 lm/W                                          |
| Life time estimate           | 3SDCM 50000h L90 B10<br>Ta 25°C                  |
| Protocol                     | On/Off                                           |
| Energy efficiency class      | E                                                |
| Dimension                    | Ø114 mm                                          |
| IP Grade                     | IP65                                             |
| Power supply                 | 220-240V 50-60Hz                                 |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS



