

**Mini Track - IPipedi 55/300h
decentralized**

code PP119L.927F/01

**PRODUCT DESCRIPTION**

Lighting fixtures with indoor track characterized by a sectional tube made of extruded aluminum 55 mm in diameter. Led cob cri>90. Color finish white. Degree of protection IP20. Decentralization version complete with cable length of 4000mm plus ceiling fixing element.

PRODUCT SPECS

Installation method	Mini Track
Light source	LED
Absorbed power	12 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Flood 24°
Finishing	White
Luminous flux of the product	1325 lm
Luminous efficiency	110 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Protocol	On/Off
Energy efficiency class	D
Weight	1.30 Kg
Dimension	H300 Ø55 mm
Power supply	220-240V 50-60Hz

WEB PAGE**ASSEMBLY
INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1