

## Ibrida wall 1800 2 spots

code IB026.930S/01



### PRODUCT DESCRIPTION

Lamp wall h 1800 mm. composed of an extruded aluminum profile. 2 led spot 16 W each. Power supply included. Color finish white. Protection class IP20.

### PRODUCT SPECS

|                              |                             |
|------------------------------|-----------------------------|
| Installation method          | Wall surface mounted        |
| Light source                 | LED                         |
| Absorbed power               | 2x8 W                       |
| Color temperature            | 3000K                       |
| Color rendering index CRI    | >90                         |
| Optic                        | Spot 19°                    |
| Finishing                    | White                       |
| Luminous flux of the product | 1329 lm                     |
| Luminous efficiency          | 83 lm/W                     |
| MacAdam color tolerance      | 2                           |
| Life time estimate           | 2SCDM 50.000h L90 B10 ta25° |
| Protocol                     | On/Off                      |
| Energy efficiency class      | D                           |
| Dimension                    | L40xW126xH1800 mm           |
| IP Grade                     | IP20                        |
| Power supply                 | 220-240V 50-60Hz            |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS



## OPTIONAL ACCESSORIES

### Ibrida Command Module



code IB100/01

Light switch and dimming accessory module that allows you to control the switching on, switching off and intensity of the light itself, directly on the product.

Technical Sheet

