



Minifile mix ceiling direct light with Leva

code MM012.935W/01























PRODUCT DESCRIPTION

Indoor direct light ceiling lamp made of extruded aluminum 6060, complete with LED; color rendering index CRI >90. IP20 degree of protection

PRODUCT SPECS

Light source LED Absorbed power 15x2,2 W / 2x8 W Color temperature 3500K Color rendering index CRI >90 Optic Wide 50° Finishing White box - black optic Luminous flux of the product 2701 lm / 1390 lm Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° L90B10 / 3SDCM 50000l L90 B10 Ta 25°C
Color temperature 3500K Color rendering index CRI >90 Optic Wide 50° Finishing White box - black optic Luminous flux of the product 2701 lm / 1390 lm Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate L90B10 / 3SDCM 500000
Color rendering index CRI >90 Optic Wide 50° Finishing White box - black optic Luminous flux of the product 2701 lm / 1390 lm Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate L90B10 / 3SDCM 50000l
Optic Wide 50° Finishing White box - black optic Luminous flux of the product 2701 lm / 1390 lm Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate L90B10 / 3SDCM 50000l
Finishing White box - black optic Luminous flux of the product 2701 lm / 1390 lm Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate L90B10 / 3SDCM 50000l
Luminous flux of the product 2701 lm / 1390 lm Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate L90B10 / 3SDCM 50000l
Luminous efficiency 82 lm/W / 87 lm/W MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate LyoB10 / 3SDCM 50000l
MacAdam color tolerance 2 / 3 50000h Ta 25° Life time estimate L90B10 / 3SDCM 50000l
50000h Ta 25° Life time estimate L90B10 / 3SDCM 50000l
Life time estimate L90B10 / 3SDCM 50000l
Protocol On/Off
Energy efficiency class E
Weight 2.20 Kg
Dimension L1140xH92 mm
IP Grade IP20
Power supply 220-240V 50-60Hz

WEB PAGE

