

Mini Sight Frame 3

code MS30.935S/01



















PRODUCT DESCRIPTION

Square recessed fixture with frame, 3 lamps. Adjustable pull-out optic

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	3x12 W / 3x18 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Spot 15°
Finishing	White
Luminous flux of the product	3855 lm / 4797 lm
Luminous efficiency	107 lm/W / 89 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Protocol	On/Off
Energy efficiency class	D
Weight	1.50 Kg
Dimension	L302xW110xH135 mm
IP Grade	IP20
Protection Class	Class III appliance
Product Spec	Rectangular shape
Dower cumply/Transformer	Not included
Power supply/Transformer	1 tot moradod
Protocol	See power supply



Ø55

WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Box mini sight 3

code MSC03

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit MINI sight 3.



