

## Minifile Openlight Track With

code MO120.830D/01



### PRODUCT DESCRIPTION

Lamp with direct and diffused light from indoor track made of extruded aluminum 6060; complete with led; color rendering index CRI >90. Professional LED modules assembled and wired on extruded aluminum heatsink equipped with harmonic steel springs for installation in the profile Tools free, wiring through 5 cables with quick-release terminal blocks; protocol Dimmable Dali. Lamp with color finish white; white opal polycarbonate screen. Degree of protection IP40/IP43.

### PRODUCT SPECS

|                              |                                         |
|------------------------------|-----------------------------------------|
| Installation method          | Track                                   |
| Light source                 | LED                                     |
| Absorbed power               | 12,8 W                                  |
| Color temperature            | 3000K                                   |
| Color rendering index CRI    | >90                                     |
| Finishing                    | White                                   |
| Luminous flux of the product | 1200 lm                                 |
| Luminous efficiency          | 94 lm/W                                 |
| MacAdam color tolerance      | 3                                       |
| Life time estimate           | 50000h Ta 25° L80 B10                   |
| Protocol                     | Dimmable Dali                           |
| Energy efficiency class      | E                                       |
| Dimension                    | L580 mm                                 |
| IP Grade                     | Inst. Parete Ip40 / Inst. Soffitto Ip43 |
| Power supply                 | 220-240V 50-60Hz                        |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

