



Leva 3 Tilt Version Trimless - kit

code LV041K.930WD/01



















PRODUCT DESCRIPTION

Fix and adjustable projectors programme for chip on board LED sources. Mounting options: with frame and trimless recessed, ceiling and wall-mounted, 230V Eurostandard track and within the Lucifero's Container for Minifile and File 2. Fixture's body in painted extruded aluminum. Optical group complete with chip on board led, lens, antiglare housing and driver (except recessed versions and 1x and 3x ceiling/wall-mounted versions). Adjustable version for ceiling/ wall mounting and for insertion within the Container for Minifile provided with special patented Soft Rotate & Slide mechanism, that allows the projector's extraction and aiming of 350° on the vertical axis and of 350° on the horizontal axis. Adjustable version for insertion within the Container for File 2 provided with special tilt mechanism, that allows the projector's extraction and aiming of +/-45° on the horizontal axis. Spot, flood and wide optics. UGR<19. Degree of protection IP23/43.

PRODUCT SPECS

Light source LED Absorbed power 3x2,2 W Color temperature 3000K Color rendering index CRI >90 Optic Wide 50° Finishing White box - black optic Luminous flux of the product 497 lm Luminous efficiency 75 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm IP Grade IP20	Installation method	Trimless recessed
Color temperature 3000K Color rendering index CRI >90 Optic Wide 50° Finishing White box - black optic Luminous flux of the product 497 Im Luminous efficiency 75 Im/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Light source	LED
Color rendering index CRI >90 Optic Wide 50° Finishing White box - black optic Luminous flux of the product 497 lm Luminous efficiency 75 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Absorbed power	3x2,2 W
Optic Wide 50° Finishing White box - black optic Luminous flux of the product 497 lm Luminous efficiency 75 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Color temperature	3000K
Finishing White box - black optic Luminous flux of the product 497 lm Luminous efficiency 75 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Color rendering index CRI	>90
Luminous flux of the product 497 lm Luminous efficiency 75 lm/W MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Optic	Wide 50°
Luminous efficiency75 lm/WMacAdam color tolerance2Life time estimate50000h Ta 25° L90B10ProtocolDimmable DaliEnergy efficiency classEWeight1.23 KgDimensionL100xW75xH110+38 mmHole size98X118 mm	Finishing	White box - black optic
MacAdam color tolerance 2 Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Luminous flux of the product	497 lm
Life time estimate 50000h Ta 25° L90B10 Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Luminous efficiency	75 lm/W
Protocol Dimmable Dali Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	MacAdam color tolerance	2
Energy efficiency class E Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Life time estimate	50000h Ta 25° L90B10
Weight 1.23 Kg Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Protocol	Dimmable Dali
Dimension L100xW75xH110+38 mm Hole size 98X118 mm	Energy efficiency class	E
Hole size 98X118 mm	Weight	1.23 Kg
	Dimension	L100xW75xH110+38 mm
IP Grade IP20	Hole size	98X118 mm
	IP Grade	IP20
Product Spec Adjustable	Product Spec	Adjustable
Power supply 220-240V 50-60Hz	Power supply	220-240V 50-60Hz

WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORY ACCORDING TO THE TYPE OF INSTALLATION

Box Leva 3 trimless tilting



code LV003B/01

Trimless recessed uncategorized wallbox for brick wall / wallbox for false ceiling. Bianco finishing wallbox for brick wall / wallbox for false ceiling

