

Leva 15 trimless recessed - kit

code LV015K.927S/01



















456



PRODUCT DESCRIPTION

Luminaire for integrated LED Chip On Board sources. Flush-mounted installation. Luminaire body in extruded painted aluminium white. Optical units complete with LED chip on board, lens, anti-glare housing. Optics 20° UGR<16. Degree of protection IP20.

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	15x2,2 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Spot 20°
Finishing	White
Luminous flux of the product	2978 lm
Luminous efficiency	90 lm/W
MacAdam color tolerance	2
Life at at a	
Life time estimate	50000h Ta 25° L90B10
Energy efficiency class	50000h Ta 25° L90B10 E
Energy efficiency class	E
Energy efficiency class Weight	E 0.30 Kg
Energy efficiency class Weight Dimension	E 0.30 Kg L450xW27xH60 mm
Energy efficiency class Weight Dimension Hole size	E 0.30 Kg L450xW27xH60 mm 32X458 mm
Energy efficiency class Weight Dimension Hole size IP Grade	E 0.30 Kg L450xW27xH60 mm 32X458 mm IP20
Energy efficiency class Weight Dimension Hole size IP Grade Protection Class	E 0.30 Kg L450xW27xH60 mm 32X458 mm IP20 Class III appliance
Energy efficiency class Weight Dimension Hole size IP Grade Protection Class Product Spec	E 0.30 Kg L450xW27xH60 mm 32X458 mm IP20 Class III appliance Rectangular shape

WEB PAGE



ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Accessori Leva Timless box 15



code LV015A/01

Trimless recessed uncategorized wallbox for false ceiling. Bianco finishing wallbox for false ceiling



AE700.32C1.MP (Copia) (Copia)



code AE700.30C.MP-1

Electronic power supply current



OPTIONAL ACCESSORIES

Wallbox for brick wall and concrete - Leva15



code CCLV15

Formwork for masonry and concrete, suitable for Leva15. Internal length 457mm - external length



