


Sight Minimal 2M

code LT4304M.927S/01





PRODUCT DESCRIPTION

Recessed downlight for wall and ceiling installation, IP20/IP23, adjustable, for accent lighting. Available in version with frame or trimless. Body optical group and frame in painted or chromed metal. Optical group adjustable 355° vertically and +/- 40° horizontally. Remote power-supply available as an accessory. Multi-lamp models set up for separate switching. It can also be completed with painted metal box for ceiling and hanging installation. It can also be installed in concrete or brick walls through specific galvanized steel wall-box, available as an accessory.

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	2x17 W / 2x24,3 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Spot 15°
Finishing	White
Luminous flux of the product	3440 lm / 4919 lm
Luminous efficiency	101 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 ta 25°C
Protocol	On/Off
Energy efficiency class	D / E
Dimension	L332xW159xH177 mm
IP Grade	IP20
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply



WEB PAGE



ASSEMBLY INSTRUCTIONS




Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Accessori Wallbox Frame Incas 2AM



code TEIN02M

Inspectable frame to be fit plaster in plasterboard 15mm thick for the article INCAS 12M, INCAS 2AM.
For plasterboard 13 mm tick it is necessary thicken.

Technical Sheet

