

## File Flex system - 3D Led line for A and C curves

code FX260.830



### PRODUCT DESCRIPTION

REGISTERED DESIGN - File Flex is a versatile extruded aluminium profile, which can design infinite shapes. Its asymmetrical section is designed to realize unique lighting effects meanwhile ensuring optimal illumination levels. The linear LED source screened by a flexible opal extruded silicone diffuser creates seamless lighting effects. The system allows the use of blind modules, multi-optic from Leva series or adjustable spot from Spot Focus series Ø26 and Ø36. It has to be completed by stabilized drivers 24V or 48V.

### PRODUCT SPECS

|                              |                  |
|------------------------------|------------------|
| Installation method          | system           |
| Light source                 | Linea Led        |
| Absorbed power               | 11 W             |
| Color temperature            | 3000K            |
| Color rendering index CRI    | >90              |
| Luminous flux of the product | 1507 lm          |
| Luminous efficiency          | 137 lm/W         |
| Protocol                     | On/Off           |
| Energy efficiency class      | D                |
| Dimension                    | W500 mm          |
| IP Grade                     | IP20             |
| Power supply/Transformer     | Not included     |
| Protocol                     | See power supply |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.  
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.  
We reserve the right to make changes to our products at any time.

Page 1 / 1