

Iground Fixed 60

code IG002A.927W/20






















65 Ø 84



PRODUCT DESCRIPTION

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available upupon request. Cylindrical outer casings available. IP67.

PRODUCT SPECS

Light source LED Absorbed power 6,7 W Color temperature 2700K Color rendering index CRI >90 Optic Wide 36° Finishing Brushed steel Luminous flux of the product 581 lm Luminous efficiency 87 lm/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included Protocol See power supply	Installation method	Floor
Color temperature 2700K Color rendering index CRI >90 Optic Wide 36° Finishing Brushed steel Luminous flux of the product 581 Im Luminous efficiency 87 Im/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Light source	LED
Color rendering index CRI >90 Optic Wide 36° Finishing Brushed steel Luminous flux of the product 581 Im Luminous efficiency 87 Im/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Absorbed power	6,7 W
Optic Wide 36° Finishing Brushed steel Luminous flux of the product 581 Im Luminous efficiency 87 Im/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Color temperature	2700K
Finishing Brushed steel Luminous flux of the product 581 Im Luminous efficiency 87 Im/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Color rendering index CRI	>90
Luminous flux of the product Luminous efficiency 87 lm/W SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Product Spec Walk-over, Circular shape Power supply/Transformer SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg L2000xH65 Ø84 mm Class III appliance Walk-over, Circular shape	Optic	Wide 36°
Luminous efficiency B7 Im/W Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Finishing	Brushed steel
Life time estimate 3SDCM 50000h L90 B10 Ta 25°C Energy efficiency class D Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Luminous flux of the product	581 lm
Energy efficiency class Weight Dimension Hole size Protection Class Product Spec Power supply/Transformer Ta 25°C D 0.3 Kg 0.3 Kg 1.2000xH65 Ø84 mm 1.2000xH65 Ø86 mm 1.200	Luminous efficiency	87 lm/W
Weight 0.3 Kg Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Life time estimate	
Dimension L2000xH65 Ø84 mm Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Energy efficiency class	D
Hole size 73 mm IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Weight	0.3 Kg
IP Grade IP67 Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Dimension	L2000xH65 Ø84 mm
Protection Class Class III appliance Product Spec Walk-over, Circular shape Power supply/Transformer Not included	Hole size	73 mm
Product Spec Walk-over, Circular shape Power supply/Transformer Not included	IP Grade	IP67
Power supply/Transformer Not included	Protection Class	Class III appliance
. care cappy, cameronia	Product Spec	Walk-over, Circular shape
Protocol See power supply	Power supply/Transformer	Not included
	Protocol	See power supply

WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Box IGround 60



code CCIG02 uncategorized

