




## File suspension with Leva group direct or direct/indirect light

code F1342.935ZD/01



## PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060, color rendering index CRI >90. Equipped with 2 groups Lever 5 spot series with high color rendering LED sources; 22 W temperature 3500K; fixed optics with aperture ; protocol Dimmable Dali. Lamp with finish: white box - black optic. Degree of protection IP20.

## PRODUCT SPECS

|                              |                                                           |
|------------------------------|-----------------------------------------------------------|
| Installation method          | Suspension                                                |
| Light source                 | LED                                                       |
| Absorbed power               | 10x2,2 W / 22 W                                           |
| Color temperature            | 3500K                                                     |
| Color rendering index CRI    | >90                                                       |
| Optic                        | Asymmetric                                                |
| Finishing                    | White box - black optic                                   |
| Luminous flux of the product | 1903 lm                                                   |
| Luminous efficiency          | 87 lm/W                                                   |
| MacAdam color tolerance      | 2                                                         |
| Life time estimate           | 50000h Ta 25°<br>L90B10 / 3SDCM 50000h<br>L90 B10 Ta 25°C |
| Protocol                     | Dimmable Dali                                             |
| Energy efficiency class      | E / D                                                     |
| Weight                       | 2.40 Kg                                                   |
| Dimension                    | L1140 mm                                                  |
| IP Grade                     | IP20                                                      |
| Power supply                 | 220-240V 50-60Hz                                          |

**WEB PAGE**



## ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

Page 1 / 1