


## File suspension with Leva group direct or direct/indirect light

code F1344.930S/01



### PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060, color rendering index CRI >90. Equipped with 3 groups Lever 5 spot series with high color rendering LED sources; 33 W temperature 3000K; fixed optics with aperture ; protocol On/Off. Lamp with finish: white box - black optic. Degree of protection IP20.

### PRODUCT SPECS

|                              |                                                           |
|------------------------------|-----------------------------------------------------------|
| Installation method          | Suspension                                                |
| Light source                 | LED                                                       |
| Absorbed power               | 15x2,2 W / 22 W                                           |
| Color temperature            | 3000K                                                     |
| Color rendering index CRI    | >90                                                       |
| Optic                        | Spot                                                      |
| Finishing                    | White box - black optic                                   |
| Luminous flux of the product | 3255 lm / 2170 lm                                         |
| Luminous efficiency          | 99 lm/W                                                   |
| MacAdam color tolerance      | 2                                                         |
| Life time estimate           | 50000h Ta 25°<br>L90B10 / 3SDCM 50000h<br>L90 B10 Ta 25°C |
| Protocol                     | On/Off                                                    |
| Energy efficiency class      | E / D                                                     |
| Weight                       | 3.70 Kg                                                   |
| Dimension                    | L1700 mm                                                  |
| IP Grade                     | IP20                                                      |
| Power supply                 | 220-240V 50-60Hz                                          |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.  
We reserve the right to make changes to our products at any time.

Page 1 / 1